

# DISPLAY 50952

## SPECIFICATIONS

|                      |                 |
|----------------------|-----------------|
| Assist               | <b>5 steps</b>  |
| Battery              | <b>5 levels</b> |
| Light on/off         | <b>Yes</b>      |
| Walk-assist protocol | <b>Yes</b>      |
| Plug                 | <b>V1</b>       |
| Color LED            | <b>IP 66</b>    |
| Position             | <b>Blue</b>     |
|                      | <b>Left</b>     |

## ADDITIONAL DATA

|               |              |
|---------------|--------------|
| Rated voltage | <b>36/48</b> |
| Weight (g)    | <b>70</b>    |

## MOUNTING PARAMETERS

|                   |               |
|-------------------|---------------|
| Holder (mm)       | <b>Ø21</b>    |
| Cable length (mm) | <b>750 mm</b> |
| Connector         | <b>V1</b>     |

## INDICATION INFORMATION

|                     |                  |
|---------------------|------------------|
| Display type        | <b>LED</b>       |
| Capacity indication | <b>Yes</b>       |
| Walk assist         | <b>Yes</b>       |
| Backlight           | <b>No</b>        |
| Error indication    | <b>LED flash</b> |

## INTERFACE

|          |           |
|----------|-----------|
| Buttons  | <b>3</b>  |
| Throttle | <b>No</b> |

## TESTS & CERTIFICATIONS

|                |                                     |
|----------------|-------------------------------------|
| IP             | <b>IP 65</b>                        |
| Certifications | <b>CE / EN 15194 / REACH / ROHS</b> |

## DIMENSIONS

